



Applications and Features

- Compact three-speed gear box with high, medium, and low speed.
- Weigh Only 6.9 Kg (15 lbs).
- D-style handle for ergonomic control.
- Multi-position front handle.
- Built-in on/off switch with motor overload protection.
- Portable Residual Current Device (P.R.C.D.) automatically shuts off electricity in the event of electric leakage.
- Tool kit including a wrench.
- Optional spindle adaptor available.

- Two Spirit Levels
- Variable speed trigger for hand held use



Switches for rig mounted mode

Hand Held Drill Motor: HH1531 Hand Held Bit Capacity: 60 mm (2.3")



Carry case and tools included.

Specifications

Rated Input	1,600 W
Voltage	AC 110-120 V • 220-240 V, 50/60 Hz
Speeds	3
Spindle Revolutions at No Load (rpm)	900/2,100/4,150 (110-120V) • 1,000/2,500/4,900 (220-240V)
Spindle Revolutions at Rated Load (rpm)	720/1,800/3,600 (110-120V) • 730/1,800/3,600 (220-240V)
Recommended Core Bit Diameter in Handheld Mode	12 to 60 mm (0.47" to 2.3")
Recommended Core Bit Diameter inRig Mounted Mode	12 to 180 mm (0.47" to 7")
Spindle Thread	G1/2" (BSPP1/2")
Weight	6.9 kg (15 lbs)

Specifications and products appearances are subject to change without prior notice.

The diamond core bit in the picture is not included in the item.