

Applications and Features

- Ideal machine for middle to large size jobs.
- Multi-position water swivel inlet for convenience.
- Right and left hand feed handle positions.
- Built-in on/off switch with motor overload protection.
- Portable Residual Current Device (P.R.C.D.) automatically shuts off electricity in the event of electric leakage. (220-240 V only)
- Normal Stand Column: 1003 mm (39") with 633 mm (25") stroke.
AB61 Column: 1060 mm (41") with 655 mm (26") stroke.
- 60 mm (2-3/8") square column.
- Tool kit including wrenches and allen keys.



AB61 swivel base available as option

Stand: TS-405

Motor: H2221

Maximum Bit Capacity: 400 mm (16") with 30 mm Spacer

Specifications

Height	1003 mm • 1060 mm (AB61)
Base Size	176 x 275 mm • 186 x 250 mm (AB61)
Available Stroke	633 mm • 655 mm (AB61)
Rated Input	3,240 W (120 V) • 3,450 W (220-240 V)
Voltage	AC 120 V • 220-240 V, 50/60 Hz
Speed	2
Spindle Revolutions at No Load (rpm)	300 / 700 (120 V) • 350 / 850 (220-240 V)
Spindle Revolutions at Rated Load (rpm)	230 / 550 (120 V) • 190 / 460 (220-240 V)
Max. Applicable Core Bit Diameter	400 mm
Spindle Thread	A-Rod Only
Weight excl. plug and cord	H2221 w carriage block: 16.9 kg • TS-405: 14.8 kg

Specifications and products appearances are subject to change without prior notice.

The diamond core bit in the picture is not included in the item.