



Applications and Features

- Automatically feeds the drill motor.
- Two modes for automatic feeding:
 - » Full-Auto Feed Mode:
Automatic feeding starts from the initial cutting process.
 - » Semi-Auto Feed Mode:
Automatic feeding starts after the initial cut is made manually.
- Automatically adjusts feeding speed according to the set drill motor load.
- Actual Drill Depth Display shows the drilling depth in real time.
- Mountable on both the right and left sides of the carriage block.
- Four Automatic Stop Functions:
 - » Automatically stops by drill depth setting
 - » Automatically stops with the stopper (Optional Accessory)
 - » Automatically stops upon workpiece penetration
 - » Automatically stops by rebar detection*

* This function operates only when certain conditions are met.

Important Note

- This product is NOT CE certified.
- Always keep eyes on the machine during operations.
Never leave the machine running alone.
In emergency, always stay at the position where the operator can stop the machine immediately.



Setting example
The motor, the stand, and the core bit are not included in the item.

Automatic Feeding Unit: AFS-P

Specifications

Voltage	AC 100-120V • 220-240V, 50/60 Hz
Rated Input	40 W
Weight	6.5 kg (100-120 V) / 6.0 kg (220-240 V)
Dimension	194 mm (W) x 258 mm (L) x 268 mm (H)
Applicable Model	TS-255 / TS-405 / TS-605

Specifications and products appearances are subject to change without prior notice.